Australian / New Zealand Distributor-----

Machinery Vibration Specialists Aust P/L 121 St. Johns Avenue GORDON NSW 2072

Ph: +61-2-9880-2422 Fx: +61-2-9880-2466

Em: mvsaust@ozemail.com.au

Web: www. MachineryVibrationSpecialists.com.au

PORTABLE EQUIPMENT

N130











**VIBROMETER** 

**MACHINE ANALYSER** 

**SPECTRUM** ANALYSER

NEW







# STANDARD ACCESSORIES

No.1 accelerometer transducer 100mV/g

No.1 magnetic base Ø 25mm

No.1 probe

No.1 transducer connection cable L 2m

No.1 USB stick with manuals

Battery charger with multiplug adapters

Carrying case

Micro USB Cable

# **OPTIONAL ACCESSORIES**

No.1 Photocell complete with upright and magnetic base

No.1 Connection cable 5m for transducer

No.1 Connection cable 5m for photocell

No.1 Extension cable 10m for transducer

No.1 Extension cable 10m for photocell



The smart solution for vibration analysis

Intuitive functions under full control


10 KHz Vibrometer and Machine Analyzer

4.3" color graphic display
 Very high luminosity and contrast for sunlight use
 Wide view angle

- Enhanced click keyboard
   Optimal tactile feedback
   Designed for gloves use
- Heavy duty and metallic connectors
- Fast measure
- Huge memory space
   14.8 GByte, expandible to 128 GByte
   1000+ measures for each type
- Screenshot display capture and save
  Smart route data store
  Output file: JSON format
  Micro USB 2.0 data port

հախ

# **VIBROMETER & TACHO**



- Big readable characters
- Overall with main peak
- 1x fundamental with phase
- Speed rotation

# **SMART ANALYSIS**



- Machine troubleshoot at a glance
- Vibration root cause identification
- Step by step according ISO10816-3
- Automatic speed detection

# HIGH RESOLUTION FFT



- Graphic zoom
- Peak cursors
- Autoscale feature
- List of main peaks

# **BEARING ANALYSIS**



- Based on envelope algorithm
- Bearing condition evaluation
- Store CBA value for trend analysis and predictive maintenance

# INTELLIGENT DATA SAVING



STEP 1: Enter the machine name



STEP 2: Select the bearing



STEP 3: Enter the X, Y or Z direction



#### **GENERAL CHARACTERISTICS**

- Display: 4,3" colour LED-backlit TFT LCD (480 x 272 pixel)
- New EasyClick tactile keyboard with embossed keys
- Internal memory: 14,8 Gb (expandible to 128 Gb)
- Multi languages user interface

#### **MEASUREMENT TYPES**

- Effective value (RMS)
- Peak value (Pk)
- Peak-to-peak value (PP)

### **MEASURING PERFORMANCE**

- Bandwidth: 1-10 KHz
- FFT Resolution: Max 3200 lines
- Tacho: Up to 250000 rpm

#### **UNITS OF MEASUREMENT**

- Acceleration: [g]
- Velocity: [mm/s] or [inch/s]
- Displacement: [µm] or [mils]
- Frequency: [Hz] or [Cpm]

#### **INPUT**

- 1 measuring channels IEPE sensor, accelerometer and velomitor.
   With a specify cable pluggable on a BNC for read any dinamic signal max. 10V PkPk
- 1 photocell channel (velocity and angle reference)
- 1 MicroUSB 2.0 port for data transfer
- 1 jack plug for battery charger

#### **AMBIENT**

- Temperature: from -20° to +70° C
- Air humidity: from 0 to 95% without condensate
- Protection: IP54

# **POWER SUPPLY**

- Long Life Battery: > 8 hours based on typical use
- Charging time: 2,5 hours for 80% recharge
   4 hours for 100% recharge
- Rechargeable 3100 mAh Lithium battery
- Power supply-battery charger for 100-240 V, 50/60 Hz (24 V, 1.5 A)

#### CARRYING CASE DIMENSIONS AND WEIGHT

Approx. 370(L) x 300 (H) x 115(D) 1800 g



CEMB S.p.A. - Via Risorgimento, 9 23826 Mandello del Lario (LC) - Italy www.cemb.com



# **Vibration analysis division:** Phone +39 0341 706111

e-mail: stm@cemb.com







Australian / New Zealand Distributor-----

Machinery Vibration Specialists Aust P/L 121 St. Johns Avenue GORDON NSW 2072

Ph: +61-2-9880-2422 Fx: +61-2-9880-2466

Em: mysaust@ozemail.com.au

Web: www. MachineryVibrationSpecialists.com.au